

EMC Celerra NS-120 Unified Storage



EMC® Celerra® NS-120 systems can be integral elements of a comprehensive information lifecycle management strategy—a strategy that helps your enterprise attain the maximum value from its information, at the lowest TCO, at every point in the information lifecycle. Information lifecycle management maps the right service level to the right application at the right cost—at the right time.

Technical Specifications

Architecture

The NS-120 unified storage platform supports both single and dual X-Blade configurations. Dual X-Blade configurations can be deployed in Primary/Primary mode for highest performance or Primary/Standby for additional hardware availability protection (i.e. X-Blade failover). The NS-120 uses proven backend EMC CLARiiON® CX4 array technology.

Each X-Blade consists of the following:

- Dual 2.8 GHz LV Intel® Xeon® processors
- 4 GB Double Data Rate RAM (266 MHz) on an 800 MHz FSB
- Two 4 Gb/s Fibre Channel ports for switch connectivity
- Up to two 4 Gb/s Fibre Channel port for tape connectivity
- Four 10/100/1000 BaseT ports or two 10 Gigabit Ethernet optical ports and two 10/100/1000 BaseT ports
- One 10/100/1000 management port
- Instance of DART File Server software

Single X-Blade configurations can be upgraded non-disruptively to dual X-Blade configurations.

Backend Array I/O Connectivity

For IP connectivity, one pair of storage processors (SP)—configuration per SP:

- Two 4 Gb/s Fibre Channel* ports for X-Blade connectivity
- One 4 Gb/s Fibre Channel* port for backend disk connectivity

EMC UltraFlex™ I/O modules for additional host connectivity per storage processor, subject to slot limits:

- Option 1: Four 4 Gb/s or 8 Gb/s Fibre Channel* (FC) ports for FC host or MPFS connectivity
- Option 2: Four 4 Gb/s or 8 Gb/s Fibre Channel* (FC) ports for host connectivity and two 1 Gb/s iSCSI ports for MirrorView™/A support
- Option 3: Four 1 Gb/s iSCSI ports for MPFS connectivity

*FCP SCSI-3 protocol, FC-AL, and FC-SW support with command tag queuing up to 256 tags

SP System Memory and CPU

- Two storage processors per NS-120 platform
- 3 GB of memory per storage processor

Maximum Cable Lengths

Shortwave optical OM2: 50 meters (8 Gb), 100 meters (4 Gb), 300 meters (2 Gb), and 500 meters (1 Gb)
Shortwave optical OM3: 150 meters (8 Gb), 380 meters (4 Gb), 500 meters (2 Gb), and 860 meters (1 Gb)

Backend (Disk) Connectivity

Each storage processor connects to one of a redundant pair of 4 Gb/s Fibre Channel buses, providing continuous drive access to hosts in the event of a storage processor or bus fault

The NS-120 requires a minimum of five drives (Fibre Channel or 7,200 rpm SATA) and supports a maximum of 120 disk drives in eight disk expansion chassis



Platform managed by a control station:

- Connection to each X-Blade via 10/100/1000 interface
- Manages X-Blade failover
- Manages all file systems via GUI
- SNMP MIB II manageability
- Secure Shell (SSH) for remote access
- HTTP server management interface
- Dual USB, 250 GB drive, DVD drive
- Single control station contains a 3.4 GHz Single Core Xeon CPU with 800 MHz FSB, 2 MB cache, and 2 GB memory

NS-120 comes with integrated CLARiiON® storage with the following drive attributes:

- Six (includes a hot spare) to 120 disks in up to eight drive trays. Each tray can be configured with:
 - FC drives
 - SATA II drives
 - Flash drives

DART File Server Facilities**Protocols Supported**

- NFSv2, v3, and v4, CIFS (SMB 1 and SMB 2), FTP, FTP Secure, iSCSI, Fibre Channel, and MPFS
- Network Lock Manager (NLM) v1, v3, v4
- Routing Information Protocol (RIP) v1–v2
- Simple Network Mgmt Protocol (SNMP)
- Network Data Mgmt Protocol (NDMP) v1–v4
- Address Resolution Protocol (ARP)
- Internet Control Message Protocol (ICMP)
- Network Time Protocol (NTP) client
- Simple Network Time Protocol (SNTP)
- Kerberos Authentication
- Lightweight Directory Access Protocol (LDAP)

Optional DART Software Facilities

- Celerra Event Enabler
 - Celerra Anti-virus
 - Celerra Event Publishing Agent
- Celerra Replicator™
- Celerra Manager Advanced Edition
- Celerra File-Level Retention
 - Celerra File-Level Retention—Enterprise
 - Celerra File-Level Retention—Compliance
- Celerra Multi-Path File System (MPFS)

Note: Celerra Manager-Basic, Virtual Provisioning, Deduplication, and SnapSure™ are bundled.

Client Connectivity Facilities

- File access by FTP, NFS, CIFS and MPFS
- Block access by iSCSI and Fibre Channel
- Virtual Data Movers for Windows clients
- Ethernet Trunking
- Link Aggregation (IEEE 802.3ad)
- Virtual LAN (IEEE 802.1q)
- UNIX archive utilities (tar/cpio)
- Network Status Monitor (NSM) v1
- Portmapper v2
- Network Information Service (NIS) Client
- Supports Microsoft DFS as Leaf node or Root Server
- NT LAN Manager (NTLM)
- LDAP signing for Windows
- Native Windows 2000/2003/2008 support
- Microsoft Windows Server 2003 Access-based Enumeration (ABE)

Optional CLARiiON Software Facilities

- Navisphere®
- Navisphere Analyzer
- Navisphere Quality of Service Manager (NQM)
- SnapView™
- MirrorView/A and MirrorView/S
- PowerPath®
- SAN Copy™

High-Availability Features

NS-120 X-Blade Enclosure

- Redundant power supplies for X-Blades
- Hot-swappable power and cooling
- Internal environmental status monitoring

DART Software Capabilities

- Ethernet Trunking
- Link Aggregation
- Failsafe Networking
- Network interface port failover
- X-Blade failover

Control Station

- Auto-call event alerting
- Call-in remote maintenance

CLARiiON Storage

- Disk scrubbing
- Mirrored write cache with de-stage for AC power loss
- Redundant hot-swap power, bus structures and I/O subsystems
- Online global hot-spare disks
- PowerPath failover for Windows and UNIX hosts

RAID Levels

RAID 1/0: Data mirrored, then striped across four to 16 drives

RAID 5: Independent data access on three to 16 drives (with striped parity)

RAID 6: Dual parity distributed across four to 16 drives

Any combination of these RAID levels can exist on a single NS-120

RAID stripe depth configurable to 4, 16, 64, 128, or 256 sectors per disk

MetaLUNs: Storage virtualization via online LUN expansion through either striping or concatenation

Configurable global hot spares

Rebuild priority tuning: Adjustment of minimum I/O reserved for server use during rebuild

Supported Disk Drives

	73 GB 4 Gb/s Enterprise Flash Drive	400 GB 4 Gb/s Enterprise Flash Drive	146 GB 4 Gb/s	300 GB 4 Gb/s	450 GB 4 Gb/s	400 GB 4 Gb/s	450 GB 4Gb/s	600 GB 4Gb/s	1 TB 4 Gb/s	1 TB 4 G/bs (Low power)
Nominal Capacity	72.67 GB	372.5 GB	135 GB	272 GB	408 GB	372.5 GB	408 GB	545 GB	931.5 GB	931.5 GB
Formatted Capacity* (520 bytes/sector, 1 MB = 1,048,576 bytes)										
Form Factor	3.5"	3.5"	3.5"	3.5"	3.5"	3.5"	3.5"	3.5"	3.5"	3.5"
Height	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"
Rotational Speed	N/A—Solid State	N/A—Solid State	15,000 rpm	15,000 rpm	15,000 rpm	10,000 rpm	10,000 rpm	10,000 rpm	7,200 rpm	5,400 rpm
Interface	Fibre Channel	Fibre Channel	Fibre Channel	Fibre Channel	Fibre Channel	Fibre Channel	Fibre Channel	Fibre Channel	SATA	SATA
Access Time										
Average Seek	0.020 ms Read 0.020 ms Write	0.020 ms Read 0.020 ms Write	3.7 ms Read 4.2 ms Write	3.5 ms Read 4.0 ms Write	3.4 ms Read 3.9 ms Write	3.9 ms Read 4.2 ms Write	3.8 ms Read 4.4 ms Write	3.8 ms Read 4.4 ms Write	8.2 ms Read 9.2 ms Write	8.9 ms Read 8.2 ms Write
Rotational Latency	N/A—Solid State	N/A—Solid State	2 ms	2 ms	2 ms	3 ms	3.0 ms	3.0 ms	4.17 ms	4.5 ms
Nominal Power Consumption										
Operating Mode	8.4 W	8.4 W	16.5 W	18.8 W	17 W	12.1 W	9.54 W	10.07 W	12.0 W	7.4 W
Idle Mode	5.4 W	5.4 W	10.7 W	13.7 W	12 W	8.1 W	5.96 W	6.49 W	8.0 W	4.0 W
Number of Drives per Disk Expansion Chassis	2–15	2–15	2–15	2–15	2–15	2–15	2–15	2–15	2–15	2–15

*Note: The EMC FLARE® storage operating environment requires 62 GB of disk space on each of the first five drives.

Dimensions (approximate)

	NS-120 with 1 15 disk tray	Expansion Disk Tray (can add 7)	40U Rack Enclosure
Height	14.0 in. (35.6 cm), 8 NEMA units (U), including mounting rails	5.25 in. (13.34 cm) 3 NEMA units (U)	75.0 in. (190.8 cm)
Width	18.92 in. (48.06 cm); mounting bars fit standard 19-inch NEMA cabinets	17.72 in. (45.0 cm)	24.0 in. (61.1 cm)
Depth	Chassis to rear: 31.58 in. (80.21 cm)	14.00 in. (35.56 cm)	39.0 in. (99.2 cm)
Weight	SPE (max): 150 lbs (92.4 kg) (NS-120 with 1 15 disk tray)	68 lbs (30.8 kg)	Empty: 380 lbs (173 kg)

Operating Environment

Temperature:	50–104 degrees F (10–40 degrees C)
Temperature Gradient:	18 degrees F/hr (10 degrees C/hr)
Relative Humidity:	20% to 80% (non-condensing)
Altitude:	7,500 ft. (2,286.4 m) @ 104 degrees F (40 degrees C) max. 10,000 ft (3,048 m) @ 98.6 degrees F (37 degrees C) max.

Electromagnetic Emissions and Immunity

FCC Class A EN55022 Class A

CE Mark VCCI Class A (for Japan)

ICES-003 Class A (for Canada) AS/NZS 3548 Class A (for Australia/New Zealand)

EN55024 Immunity, ITE BSMI Class A (for Taiwan)

Quality and Safety Standards

UL 60950; CSAC 22.2-60950, FN 60950

Manufactured under an ISO 9000-registered quality system

ETSI EN 300 386

AC Power and Dissipation

Requirement	NS-120 with One 15-Disk Tray	Expansion Disk Tray*
AC Line Voltage	100 to 240 V AC, 50–60 Hz, single-phase	100 to 240 V AC, 50–60 Hz, single-phase
AC Line Voltage Tolerance	Voltage \pm 10%, frequency \pm 3 Hz	Voltage \pm 10%, frequency \pm 3 Hz
AC Line Current (Operating Maximum)	11.2 A max. at 100 V AC, 5.6 A max. at 200 V AC	3.8 A max. at 100 V AC, 1.9 A max. at 200 V AC
Power Consumption (Operating Maximum)	1,115 VA (970 W) max.	380 VA (365 W) max. (fully configured)*
Power Factor	0.98 min. at full load, low voltage	0.98 min. at full load, low voltage
Heat Dissipation (Operating Maximum)	3.49×10^6 J/hr, (3,400 Btu/hr) max.	1.31×10^6 J/hr, (1,250 Btu/hr) max.
In-rush Current	138 A max. for ½ line cycle, per line cord at 240 V AC 69 A max for ½ line cycle, per line cord at 120 V AC	50 A max. for ½ line cycle, per line cord at 240 V AC 25 A max. for ½ line cycle, per line cord at 120 V AC
Startup Surge Current	59 A rms max. for 50 ms, at any line voltage	15 A pk (10.6 A rms) max. for 100 ms, at any line voltage
AC Protection	10 A fuse on each power supply, both phases	10 A fuse on each power supply, both phases
AC Receptacle	IEC320-C14 appliance coupler, per power supply	IEC320-C14 appliance coupler, per power supply
Ride-through Time	30 ms min.	30 ms min.
Current Sharing	\pm 15% of full load, between power supplies	\pm 10% of full load, between power supplies

*Ratings assume fully loaded Disk Array Enclosure that includes two power supplies, two LLCs, and 15 disk drives

Warranty and Support Options

Standard three-year Enhanced Warranty: 5x9 NBD, 7x24 remote support, customer installation of replacement disk drives, power supplies, fans, and small form-factor-pluggable optical transceivers.

Optional Premium Maintenance Upgrade: 7x24 onsite support, four-hour response time commitment, critical problem escalation management, and EMC installation of replacement parts.



EMC Corporation
Hopkinton
Massachusetts
01748-9103
1-508-435-1000
In North America 1-866-464-7381
www.EMC.com