

EMC RecoverPoint Family

EMC RecoverPoint/SE V3.0 and EMC RecoverPoint V3.0

The EMC® RecoverPoint family provides cost-effective, local continuous data protection (CDP) and continuous remote replication (CRR) solutions that allow for any-point-in-time data recovery. RecoverPoint/SE is the offering that simplifies the continuous data protection and replication for a single CLARiiON® CX and CX3 UltraScale™ series of arrays. RecoverPoint is a full-featured offering that adds support for intelligent fabrics and heterogeneous server and storage platforms. Both products enable customers to centralize and simplify their data protection management and provide local continuous data protection and/or remote replication.

EMC RecoverPoint can be part of a comprehensive information lifecycle (ILM) strategy—a strategy that helps your enterprise attain the maximum value from its information, at the lowest TCO, at every point in the information lifecycle. RecoverPoint enables ILM by enhancing an enterprise’s operational recovery and disaster recovery processes, by reducing the amount of data loss, and by reducing the time required for recovery.

Features

RecoverPoint CDP

Provides block-level local replication between LUNs in the same SAN using true-CDP technology that journals every write for later recovery to any point in time.

RecoverPoint CRR

Provides block-level asynchronous remote replication between LUNs in two different SANs using near-CDP technology that journals groups of writes for later recovery to significant points in time.

RecoverPoint CLR

Provides simultaneous block-level local replication and asynchronous block-level remote replication for LUNs with one copy residing locally in the same SAN with every write journaled, and the second copy residing remotely in a different SAN with significant groups of writes journaled. Recovery of one copy can occur without affecting the other copy.

Policy-based management

SLA policies enable optimization of storage and network resources by managing recovery-point objectives (RPOs) and recovery-time objectives (RTOs) across multiple applications and their data.

Application-aware integration

Supports intelligent bookmarks for replication and CDP with application integration capabilities that leverage vendor supplied APIs, such as the Microsoft Virtual Device Interface (VDI) for SQL Server and Microsoft Volume Shadow Copy Services (VSS) for Exchange.

Reliability and Availability

RecoverPoint features are provided by an out-of-band appliance attached into the SAN for local storage access and into the IP WAN for remote replication and management. Highly available appliance configurations have no single point of failure. Each appliance supports a dual (A/B) fabric.

System Capabilities

Feature	RecoverPoint/SE	RecoverPoint
Number of RecoverPoint appliances per RecoverPoint cluster	2	2–8
Maximum LUNs supported per RecoverPoint cluster	2,048	2,048
Maximum amount of protected data	Limited to 8 TB	150 TB (controlled by license)
Maximum number of arrays supported	CDP: 1, CRR or CLR: 2 (1 local, 1 remote)	N/A
Maximum LUN size	2 TB (less 512 bytes)	2 TB (less 512 bytes)
Number of consistency groups per appliance	30	30
Number of consistency groups per RecoverPoint cluster	60	60

Connectivity

Each RecoverPoint appliance provides four physical Fibre Channel ports that are auto-sensing, supporting 1, 2, and 4 Gb/s connections. Each RecoverPoint appliance provides two 100/1000 Ethernet ports. One Ethernet port is used for management and monitoring and the other port is used for remote replication. Hosts and arrays are connected to the RecoverPoint appliance using standard Fibre Channel SANs, enabling host fan-in and array fan-out.

Interoperability

RecoverPoint/SE CDP supports protecting volumes inside a single CLARiiON CX or CX3 UltraScale series array. RecoverPoint/SE CRR supports replicating volumes between two CLARiiON CX and/or CX3 UltraScale series arrays. RecoverPoint/SE CLR supports the protection and replication of the same volume locally inside a single CLARiiON CX or CX3 UltraScale series array or between two CLARiiON CX and/or CX3 UltraScale series arrays. RecoverPoint/SE requires EMC PowerPath® for Windows for multi-path support. RecoverPoint/SE only supports the CLARiiON CX and CX3 UltraScale series. RecoverPoint supports heterogeneous server and storage platforms. Please see the EMC Support Matrix for details.

Limits and Performance

RecoverPoint/SE only supports the Windows platform using a host-based splitter driver, and supports AIX, HP-UX, Linux, Solaris, VMware®, and Windows platforms using a CLARiiON CX3-based splitter driver. RecoverPoint/SE does not support boot-from-SAN volumes. RecoverPoint/SE can be upgraded to RecoverPoint without loss of protected images. RecoverPoint supports a host-based and CLARiiON CX3-based splitter driver on multiple platforms. RecoverPoint supports intelligent fabric-based splitters available on the EMC Connectrix® AP-7600B or on the Connectrix PB-48K-AP4-18 blade installed in the Connectrix ED-48000B intelligent-switching platform or on the Connectrix MDS SSM blade installed in the Connectrix MDS 9000 family of storage switches. Please see the EMC Support Matrix for details.

Management

RecoverPoint is managed through the management IP interfaces on each RecoverPoint appliance. For high-availability support, a virtualized management IP can be assigned for remote use. Primary management is through a web-based graphical user interface (GUI) that supports HTTP or HTTPS. Interactive and programmatic command-line access (CLI) is available through SSH over SSL V3.

Physical Specifications

The RecoverPoint appliance is designed to be mounted into a standard NEMA 19-inch rack cabinet using side-mounting EMC EOU rails and/or slides.

Height (in./cm)	1.67/4.26 (fits 1U slot)
Width (in./cm)	16.7/42.6
Depth (in./cm)	30.4/77.2
Weight (lb/kg)	35.8/16.3

Power Specifications

The RecoverPoint appliance has redundant hot-swappable power supplies. An EC320-C14 inlet is provided on the rear wall of each power supply.

Input Voltage (VAC)	90/246 VAC
Frequency (Hz)	50–60 Hz
Circuit Breaker (Amps), Recommended	10
Power Drops	2

Environmental

Operating Temperature	10° C to 35° C (50° F to 95° F) 0 ft
Storage Temperature	–40° C to 65° C (–40° F to 149° F)
Operating Relative Humidity	20% to 80% Non-condensing (twmax=29C)
Maximum Humidity Gradient	10% per Hour, Operational and Non-operational Conditions
Storage Relative Humidity	5% to 95% Non-condensing (twmax=38C)
Operating Vibration	0.26 G at 5 Hz to 350 Hz for 2 Minutes
Storage Vibration	1.54 Grms Random Vibration at 10 Hz to 250 Hz for 15 Minutes
Operating Shock	1 Shock Pulse of 41 G for up to 2 ms
Storage Shock	6 Shock Pulses of 71G for up to 2 ms
Operating Altitude	–16 to 3,048 m (–50 ft to 10,000 ft)
Storage Altitude	–16 m to 10,600 m (–50 ft to 35,000 ft)

Warranty and Maintenance

Ninety-day software warranty and one-year hardware warranty is included. Software maintenance and extended hardware warranties are available.



EMC Corporation
Hopkinton
Massachusetts
01748-9103
1-508-435-1000
In North America 1-866-464-7381
www.EMC.com